


CuZn 39 Pb 3 (MS 58)

Werkstoff-Nr. / No de matière: 2.0401 EN 12167

Dreh- und Bohrqualität / qualité décolletage

Flachstangen / méplats

hart / dur
Länge 3000 mm / longueur 3000 mm



Abmessung Dimensions	kg/m
6 x 2	0.102
8 x 4	0.272
10 x 2	0.170
10 x 3	0.255
10 x 4	0.340
10 x 5	0.425
10 x 6	0.510
10 x 7	0.595
10 x 8	0.680
12 x 2	0.204
12 x 3	0.306
12 x 4	0.408
12 x 5	0.510
12 x 6	0.612
12 x 8	0.816
12 x 10	1.020
15 x 2	0.255
15 x 3	0.383
15 x 4	0.510
15 x 5	0.638
15 x 6	0.765
15 x 8	1.020
15 x 10	1.275
15 x 12	1.530
20 x 2	0.340
20 x 3	0.510
20 x 4	0.680
20 x 5	0.850
20 x 6	1.020
20 x 8	1.360

Abmessung Dimensions	kg/m
20 x 10	1.700
20 x 12	2.040
20 x 15	2.550
25 x 2	0.425
25 x 3	0.638
25 x 4	0.850
25 x 5	1.063
25 x 6	1.275
25 x 8	1.700
25 x 10	2.125
25 x 12	2.550
25 x 15	3.188
25 x 20	4.250
30 x 2	0.510
30 x 3	0.765
30 x 4	1.020
30 x 5	1.275
30 x 6	1.530
30 x 8	2.040
30 x 10	2.550
30 x 12	3.060
30 x 15	3.825
30 x 20	5.100
30 x 15	3.825
40 x 2	0.680
40 x 3	1.020
40 x 4	1.360
40 x 5	1.700
40 x 6	2.040

Abmessung Dimensions	kg/m
40 x 8	2.720
40 x 10	3.400
40 x 12	4.080
40 x 15	5.100
40 x 20	6.800
40 x 25	8.500
40 x 30	10.200
40 x 35	11.900
50 x 2	0.850
50 x 3	1.275
50 x 4	1.700
50 x 5	2.125
50 x 6	2.550
50 x 8	3.400
50 x 10	4.250
50 x 12	5.100
50 x 15	6.375
50 x 20	8.500
50 x 25	10.625
50 x 30	12.750
50 x 40	17.000
60 x 3	1.530
60 x 4	2.040
60 x 5	2.550
60 x 6	3.060
60 x 8	4.080
60 x 10	5.100
60 x 12	6.120
60 x 15	7.650

Abmessung Dimensions	kg/m
60 x 20	10.200
60 x 30	15.300
60 x 40	20.400
70 x 5	2.975
70 x 6	3.570
70 x 8	4.760
70 x 10	5.950
70 x 12	7.140
80 x 10	6.800
80 x 12	8.160
80 x 15	10.200
80 x 20	13.600
80 x 25	17.000
80 x 30	20.400
80 x 40	27.200
80 x 50	34.000
100 x 5	4.250
100 x 10	8.500
100 x 20	17.000
100 x 30	25.500
100 x 40	34.000
100 x 50	42.500
100 x 60	51.000
100 x 70	59.500
100 x 80	68.000
120 x 10	10.200
120 x 20	20.400
120 x 30	30.600
120 x 40	40.800

Formtoleranzen: EN 12167
Tolérances sur forme:

Andere Abmessungen auf Anfrage
Autres dimensions sur demande

Lieferform Stangen, Zuschnitte
Forme de livraison barres, coupes

Mechanische Festigkeitswerte EN 12167
Caractéristiques mécaniques

